

PAGE: 1

PRINT DATE: 07/07/94

**FAILURE MODES EFFECTS ANALYSIS (FMEA) - NONCRITICAL HARDWARE
NUMBER: 05-2B-22104 -X**

SUBSYSTEM NAME: COMM & TRACK: ULTRA HIGH FREQ COMM (UHF)

REVISION: 1 5/28/94

	PART NAME VENDOR NAME	PART NUMBER VENDOR NUMBER
LRU	: PANEL 06	V070-730389
SRU	: SWITCH, TOGGLE	ME452-0102-7201

PART DATA

EXTENDED DESCRIPTION OF PART UNDER ANALYSIS:
SWITCH, POWER AMP ON/OFF TOGGLE SWITCH, 2 POT

REFERENCE DESIGNATORS: 36V73A6S10

QUANTITY OF LIKE ITEMS: 1
ONE

FUNCTION:
ENABLES UHF 10 WATT PA IN SIMPLEX MODE.

FAILURE MODES EFFECTS ANALYSIS (FMEA) - NONCRITICAL FAILURE MODE
NUMBER: 05-2B-22104 - 01

REVISION# 1 5/28/94
SUBSYSTEM NAME: COMM & TRACK: ULTRA HIGH FREQ COMM (UHF)
LRU: PANEL 06
ITEM NAME: SWITCH, TOGGLE
CRITICALITY OF THIS FAILURE MODE: 1R3

FAILURE MODE:
SWITCH CONTACT FAILS OPEN

MISSION PHASE:
 PL PRELAUNCH
 LO LIFT-OFF
 OO ON-ORBIT
 DO DE-ORBIT
 LS LANDING SAFING

VEHICLE/PAYLOAD/KIT EFFECTIVITY: 102 COLUMBIA
 103 DISCOVERY
 104 ATLANTIS
 105 ENDEAVOUR

CAUSE:
 MECHANICAL FAILURE, VIBRATION, SHOCK, CONTAMINATION.

CRITICALITY 1/1 DURING INTACT ABORT ONLY? NO

REDUNDANCY SCREEN A) PASS
 B) PASS
 C) PASS

PASS/FAIL RATIONALE:
 A)
 B)
 C)

- FAILURE EFFECTS -

- (A) SUBSYSTEM:**
 (1) 3/3 EVA - NO EFFECT.
 (2) 1R/3 OTHER MISSION PHASES - POWER AMP BYPASSED IN ALL MODES: RF OUTPUT LIMITED TO 0.25 WATT.
- (B) INTERFACING SUBSYSTEM(S):**
 (1) 3/3 EVA - NO EFFECT.
 (2) 1R/3 OTHER MISSION PHASES - POWER AMP BYPASSED IN ALL MODES: RF OUTPUT LIMITED TO 0.25 WATT.

FAILURE MODES EFFECTS ANALYSIS (FMEA) -- NONCRITICAL FAILURE MODE
NUMBER: 05-2B-22104 - 01

(C) MISSION:

(1) 3/3 EVA - NO EFFECT.

(2) 1R/3 OTHER MISSION PHASES - AIR/GROUND: RANGE TO GROUND STATION LIMITED, WORST CASE IS LOSS OF UHF DOWNLINK VOICE.

(D) CREW, VEHICLE, AND ELEMENT(S):

(1) 3/3 EVA - NO EFFECT.

(2) 1R/3 OTHER MISSION PHASES - NO EFFECT DUE TO FIRST FAILURE.

(E) FUNCTIONAL CRITICALITY EFFECTS:

AFTER THREE FAILURES (THIS SWITCH AND 2 S-BAND), POSSIBLE LOSS OF CREW/VEHICLE DUE TO LOSS OF STATE VECTOR UPDATE.

-DISPOSITION RATIONALE-

(A) DESIGN:

REFER TO APPENDIX A, ITEM # 1, TOGGLE SWITCH

(B) TEST:

REFER TO APPENDIX A, ITEM # 1, TOGGLE SWITCH

GROUND TURNAROUND TEST

ANY TURNAROUND CHECKOUT TESTING IS ACCOMPLISHED IN ACCORDANCE WITH OMRSD.

(C) INSPECTION:

REFER TO APPENDIX A, ITEM # 1, TOGGLE SWITCH

(D) FAILURE HISTORY:

CURRENT DATA ON TEST FAILURES, FLIGHT FAILURES, UNEXPLAINED ANOMALIES, AND OTHER FAILURES EXPERIENCED DURING GROUND PROCESSING ACTIVITY CAN BE FOUND IN THE PRACA DATABASE.

(E) OPERATIONAL USE:

LOW POWER RECEPTION MAY BE POSSIBLE BY VEHICLE ORIENTATION.

- APPROVALS -

PAE MANAGER : K. L. PRESTON
PRODUCT ASSURANCE ENGR : T. R. CLARK
DESIGN ENGINEERING : H. D. HADDAD
NASA SSMA :
NASA SUBSYSTEM MANAGER :

K. L. Preston - 7/6/94
T. R. Clark
H. D. Haddad - 7/6/94
Michael Perry
Nancy A. Olson