

**SSME EA/CIL
REDUNDANCY SCREEN**

Component Group: Ducts and Lines
 CIL Item: K401-01
 Part Number: RES1001
 Component: Hydraulic Supply Hose
 FMEA Item: K401
 Failure Mode: Fails to contain hydraulic fluid.

Prepared: D. Early
 Approved: T. Nguyen
 Approval Date: 7/25/00
 Change #: 1
 Directive #: CCBD ME3-01-5638

Page: 1 of 1

Phase	Failure / Effect Description	Criticality Hazard Reference
M 4.1	Hydraulic fluid leakage into aft compartment. Loss of hydraulic pressure results in hydraulic lockup. Loss of mission may result when hydraulic lockup occurs during Max Q throttling. Redundancy Screens: SINGLE POINT FAILURE: N/A	1R ME-E1P,S,A,M,C,D
C 4.2	When failure occurs when MFV is less than 10%, but not closed, Channel B SEII will not occur. MFV will remain at lockup position until failsafe servoswitch is de-energized post cutoff. Open air fire if on launch pad. Loss of vehicle. Redundancy Screens: SINGLE POINT FAILURE: N/A	1 ME-E1P,S,A,M,C,D

SSME FMEA/CIL
DESIGN

Component Group: Ducts and Lines
CIL Item: K401-01
Part Number: RES1001
Component: Hydraulic Supply Hose
FMEA Item: K401
Failure Mode: Fails to contain hydraulic fluid.

Prepared: D. Early
Approved: T. Nguyen
Approval Date: 7/25/00
Change #: 1
Directive #: CCBD ME3-01-5638

Page: 1 of 1

Design / Document Reference

FAILURE CAUSE: A: Parent material failure or weld failure.
B: Damaged/defective bellows assembly.

THE LINE ASSEMBLY (1) AND BELLOWS ARE MANUFACTURED UTILIZING INCONEL 718. INCONEL 600 WAS USED FOR THE WIRE BRAID ON THE FLEXIBLE HOSE MEMBERS. INCONEL 718 WAS SELECTED FOR ITS STRENGTH, RESISTANCE TO STRESS CORROSION, CORROSION RESISTANCE, HIGH/LOW CYCLE FATIGUE CHARACTERISTICS, AND WELDABILITY (2). MATERIALS ARE HEAT TREATED TO DEVELOP FULL MATERIAL STRENGTH AND HARDNESS. THE BRAID MATERIAL WAS SELECTED FOR ITS STRENGTH AND CORROSION RESISTANCE (2). FLANGE SECTIONS INCORPORATE RADIUS JOINTS TO REDUCE STRESS CONCENTRATIONS. OFFSET LIMIT REQUIREMENTS ARE ESTABLISHED TO REDUCE STRESS CONCENTRATIONS AND IMPROVE WELD GEOMETRY. TUBING STOCK IS DRAWN TO MAINTAIN SURFACE REGULARITY. THE MAXIMUM BEND MOMENT DURING PRESSURIZATION IS SPECIFIED FOR PROPER DUCT LOADING. BRAID IS MULTI-LAYERED INTERWOVEN WIRE FOR TENSILE REINFORCEMENT TO THE PRESSURE CARRYING BELLOWS. EXTERNAL RINGS ARE USED TO IMPROVE WELD QUALITY AND SUPPORT THE WIRE BRAID AT THE SPOOL-TO-BRAID INTERFACE. INSTALLATION IS CONTROLLED FOR ANGULARITY AND OFFSET PER SPECIFICATION REQUIREMENTS (3). MINIMUM FACTORS OF SAFETY MEET CEI REQUIREMENTS (4). HIGH AND LOW CYCLE FATIGUE LIFE MEET CEI REQUIREMENTS (5). THE FLEXIBLE LINE HAS SUCCESSFULLY COMPLETED THE BENDING MOMENT, FLEXURAL ENDURANCE, ULTIMATE PRESSURE, SECTIONING, PROOF PRESSURE, FLOW RESONANCE, AND VIBRATION DVS TESTING (6). ANALYSIS SHOWED NO POTENTIAL BELLOW EXCITATION OF RESONANCE DUE TO FLOW INDUCED VIBRATION (6). THE LINE ASSEMBLY PARENT MATERIALS WERE CLEARED FOR FRACTURE MECHANICS/NDE FLAW GROWTH, SINCE THEY ARE NOT FRACTURE CRITICAL PARTS (7). TABLE K401 LISTS ALL THE FMEA/CIL WELDS AND IDENTIFIES THOSE WELDS IN WHICH THE CRITICAL INITIAL FLAW SIZE IS NOT DETECTABLE, AND THOSE WELDS IN WHICH THE ROOT SIDE IS NOT ACCESSIBLE FOR INSPECTION. THESE WELDS HAVE BEEN ASSESSED AS ACCEPTABLE FOR FLIGHT BY RISK ASSESSMENT (8).

(1) RES1001; (2) RSS-8575, RSS-8582; (3) RA1102-006; (4) RSS-8546, CP320R0003B; (5) RL00532, CP320R0003B; (6) RSS-511-9, RSS-511-31, RSS-511-45, RSS-511-47, RSS-511-48; (7) NASA TASK 117; (8) RSS-8756

**SSME FA /CIL
INSPECTION AND TEST**

Component Group: Ducts and Lines
 CIL Item: K401-01
 Part Number: RES1001
 Component: Hydraulic Supply Hose
 FMEA Item: K401
 Failure Mode: Fails to contain hydraulic fluid.

Prepared: D. Early
 Approved: T. Nguyen
 Approval Date: 7/25/00
 Change #: 1
 Directive #: CCBD ME3-01-5638

Page: 1 of 1

Failure Causes	Significant Characteristics	Inspection(s) / Test(s)	Document Reference
A, B	HYDRAULIC SUPPLY HOSE		RES1001
	MATERIAL INTEGRITY	MATERIAL INTEGRITY IS VERIFIED PER SPECIFICATION REQUIREMENTS. ALL WELDS ARE INSPECTED TO DRAWING AND SPECIFICATION REQUIREMENTS PER WELD CLASS. INSPECTIONS INCLUDE: VISUAL, DIMENSIONAL, PENETRANT, RADIOGRAPHIC, ULTRASONIC, AND FILLER MATERIAL, AS APPLICABLE.	RC1310 RL10011 RA0607-094 RA0115-116 RA0115-006 RA1115-001 RA0115-127
	HEAT TREAT	LINE HEAT TREAT IS VERIFIED PER SPECIFICATION REQUIREMENTS.	RA1611-002
	ASSEMBLY INTEGRITY	THE LOT COMPARISON TEST IS PERFORMED PER SPECIFICATION REQUIREMENTS INCLUDING: - PROOF PRESSURE. - BENDING MOMENT. - FLEXUAL ENDURANCE. - VACUUM LEAK. - SECTIONING.	RC1310 RC1310 RC1310 RC1310 RC1310
	ACCEPTANCE TESTING	A BALL CHECK IS PERFORMED ON EACH LINE PER SPECIFICATION REQUIREMENTS. LINE IS PROOF PRESSURE TESTED PER SPECIFICATION REQUIREMENTS. LINE IS MASS SPECTROMETER LEAK TESTED PER SPECIFICATION REQUIREMENTS. QUICK DISCONNECT IS PROOF PRESSURE TESTED PER DRAWING REQUIREMENTS.	RC1310 RC1310 RC1310 RE2201
	FLIGHT FLOW TESTING	FOLLOWING REPAIR OR REPLACEMENT, AN EXTERNAL LEAK CHECK IS PERFORMED TO REVALIDATE THE SUBSYSTEM. DURING EXTERNAL INSPECTIONS, THE HYDRAULIC SYSTEM IS VISUALLY INSPECTED FOR LEAKAGE. DURING AFT CLOSEOUT INSPECTION, ANY EVIDENCE OF PREVIOUS HYDRAULIC LEAKAGE REQUIRES FURTHER DISPOSITION. (LAST TEST)	OMRSD V41GEN.575 OMRSD V41BU0.030 OMRSD V41BU0.070

Failure History: Comprehensive failure history data is maintained in the Problem Reporting database (PRAMS/PRACA)
 Reference: NASA letter SA21/88/308 and Rocketdyne letter 88RC09761.

Operational Use: FAILURE MODE CAN BE DETECTED IN REALTIME BY THE FLIGHT CONTROL TEAM WHO WILL EVALUATE EFFECTS UPON VEHICLE PERFORMANCE AND ABORT CAPABILITY. BASED ON THIS EVALUATION THE APPROPRIATE ABORT MODE OR SYSTEM CONFIGURATION WILL BE SELECTED. FAILURE DETECTION CUES AND ASSOCIATED SSME PERFORMANCE DATA HAVE BEEN COORDINATED BETWEEN THE ENGINEERING AND FLIGHT OPERATIONS ORGANIZATIONS WITH THE RESPONSES DOCUMENTED IN MISSION FLIGHT RULES.

SSME EA/CIL
WELL JOINTS

Component Group: Ducts and Lines
 CIL Item: K401
 Part Number: RES1001
 Component: Hydraulic Supply Hose
 FMEA Item: K401

Prepared: D. Early
 Approved: T. Nguyen
 Approval Date: 7/25/00
 Change #: 1
 Directive #: CCBD ME3-01-5638
 Page: 1 of 1

Component	Basic Part Number	Weld Number	Weld Type	Class	Root Side Not Access	Critical Initial Flaw Size Not Detectable		Comments
						HCF	LCF	
LINE	RES1001	1,12,14	GTAW	I	X	X		
LINE	RES1001	2,5,8,11	GTAW	II	X			
LINE	RES1001	3,4,9,10	GTAW	II	X			
LINE	RES1001	6,7	GTAW	I	X			
LINE	RES1001	13	GTAW	I	X	X	X	
LINE	RES1001	15-19	GTAW	I	X			