

CRITICAL ITEMS LIST

SYSTEM: COMMUNICATIONS AND TRACKING SUBSYSTEM: SPACE TO SPACE COMMUNICATIONS SYSTEM
 ASSEMBLY: SPACE TO SPACE ORBITER RADIO (SSOR) ASS'Y P/N: SED16102581

APPROVAL DATE:
 SUPERCEDES REV: N/A DATE: N/A
 SHEET 1 OF 4

END ITEM EFFECTIVITY: OV102, OV103, OV104, OV105, AND SUBS.

PREPARED BY: Nanci A. Olson

DATE: 12/16/96

APPROVAL:

SR&MA.

DATE:

DESIGN:

DATE: 3-2-00

SSCS PROJECT MANAGER:

Mark Clump Mark Clump
Matt Lemke Matt Lemke

DATE: 5-3-00

CRITICALITY(H/F): 2/2

INTACT ABORT MODE CRIT: N/A

REDUNDANCY SCREENS: A-N/A B-N/A C-N/A

FMEA REFERENCE: SSOR-01

NAME: SSOR

DRAWING REFERENCE: SED16102581

QUANTITY: 1

CIL #	REV	FUNCTION	FAILURE MODE AND CAUSE	FAILURE EFFECT	RATIONALE FOR ACCEPTABILITY
SSOR-01	BASIC	<p>(1) Provides RF duplex voice comm between Orbiter and EMU's.</p> <p>(2) Receives biomed and telemetry from EMU</p> <p>(3) Provides RF duplex voice comm between Orbiter and Station</p> <p>(4) Provides RF command to Space Station and telemetry from Space Station</p>	<p>FAILURE MODE: Short to case of RF Input or Output at Payload Bay Antenna Port</p> <p>CAUSE: Contamination, vibration, shock, EEE parts failure, or temperature cycle</p> <p>MISSION PHASES: Pre EVA EVA Post EVA Station Rendezvous</p>	<p>SUBSYSTEM: Loss of Transmit and Receive Voice Communications between Orbiter and Station or EMUs. Loss of commands to Station. Loss of data from EMU and Station.</p> <p>INTERFACING SUBSYSTEMS: None</p> <p>MISSION: Terminate EVA. Terminate Station rendezvous.</p> <p>CREW/VEHICLE: No effect.</p> <p>SUCCESS PATHS REMAINING AFTER FIRST FAILURE: 0</p> <p>TIME TO EFFECT: minutes</p>	<p>DESIGN: The electrical design of the SSOR is based upon JSC in-house engineering model hardware. Litton is manufacturing the hardware in accordance with the appropriate NHR 5300.4 standards.</p> <p>Passive EEE parts are selected from the guidelines of MIL-STD-975. Active EEE are approved by the JSC Engineering Directorate Certified Parts Approval Process.</p> <p>The RF connector is a hermetically sealed TNC bulkhead feedthrough adapter, Amphenol Part Number 79100. The RF connector is connected to the SSOR directional coupler through a coaxial cable (RG142) with an SMA connector on the coupler end, and a TNC connector on the RF adapter end.</p> <p>TEST: CERTIFICATION: One time test on Qrel SSOR. Power output measured before, during, and after exposure to environments.</p> <p>QUALIFICATION THERMAL TEST - 7 cycles from 25F to 155F operating and 1 cycle to -65F non-operating. RF output measured before, during, and after thermal test.</p> <p>PRESSURE TEST - 8 to 15.23 psia at 3psi/minute repress/depress rate. Non-operating excursion to 50 psia. RF output measure before, during and after pressure test.</p>

CRITICAL ITEMS LIST

SYSTEM: COMMUNICATIONS AND TRACKING SUBSYSTEM: SPACE TO SPACE COMMUNICATIONS SYSTEM

ASSEMBLY: SPACE TO SPACE ORBITER RADIO (SSOR) ASS'Y P/N: SED16102581

APPROVAL DATE:

SUPERCEDES REV: N/A DATE: N/A

END ITEM EFFECTIVITY: OV102, OV103, OV104, OV105, AND SUBS.

SHEET 2 OF 4

PREPARED BY: Nanci A. Olson

DATE: 12/16/96

APPROVAL:

SR&MA:

DATE: _____

DESIGN:

DATE: _____

SSCS PROJECT MANAGER:

DATE: _____

CRITICALITY(T/F): 2/2

INTACT ABORT MODE CRIT. N/A

REDUNDANCY SCREENS: A-N/A B-N/A C-N/A

FMEA REFERENCE: SSOR-01

NAME: SSOR

DRAWING REFERENCE: SED16102581

QUANTITY: 1

CIL #	REV	FUNCTION	FAILURE MODE AND CAUSE	FAILURE EFFECT	RATIONALE FOR ACCEPTABILITY
SSOR-01	BASIC	<p>(1) Provides RF duplex voice comm between Orbiter and EMU's.</p> <p>(2) Receives biomed and telemetry from EMU</p> <p>(3) Provides RF duplex voice comm between Orbiter and Station</p> <p>(4) Provides RF command to Space Station and telemetry from Space Station</p>	<p>FAILURE MODE: Short to case of RF Input or Output at Payload Bay Antenna Port</p> <p>CAUSE: Contamination, vibration, shock, EEE parts failure, or temperature cycle</p> <p>MISSION PHASES: Pre EVA EVA Post EVA Station Rendezvous</p>	<p>SUBSYSTEM: Loss of Transmit and Receive Voice Communications between Orbiter and Station or EMUs. Loss of commands to Station. Loss of data from EMU and Station.</p> <p>INTERFACING SUBSYSTEMS: None</p> <p>MISSION: Terminate EVA. Terminate Station rendezvous.</p> <p>CREW/VEHICLE: No effect.</p> <p>SUCCESS PATHS REMAINING AFTER FIRST FAILURE: 0</p> <p>TIME TO EFFECT: minutes</p>	<p>TEST: (CONTINUED)</p> <p>SHOCK - Bench handling 4 inch drop test on each corner. Landing shock and acceleration environments certified by analysis.</p> <p>VIBRATION - Test-induced (QAVT) - 5 minutes per axis. 20 to 80 Hz - increasing 3 dB/oct; 80 to 350 Hz - constant 0.067 g²/Hz 350 to 2000 Hz - decreasing 3 dB/oct Flight-induced - 15 min. 40 sec per axis 20 to 150 Hz - increasing 6 dB/oct 150 to 1000 Hz - constant 0.03 g²/Hz 1000 to 2000 Hz - decreasing 6 dB/oct Power output measured before and after each vibration test.</p> <p>Salt-fog, humidity, and fungus certified by analysis to requirements of JSC 26799 (SSOR Specification)</p> <p><u>ACCEPTANCE:</u></p> <p>TEMPERATURE - One and one-half cycles from 30F to 130F, with power output measured at temperature extremes.</p>

CRITICAL ITEMS LIST

SYSTEM: COMMUNICATIONS AND TRACKING SUBSYSTEM: SPACE TO SPACE COMMUNICATIONS SYSTEM

ASSEMBLY: SPACE TO SPACE ORBITER RADIO (SSOR) ASS'Y P/N: SED16102581

APPROVAL DATE:

END ITEM EFFECTIVITY: OV102, OV103, OV104, OV105, AND SUBS.

SUPERCEDES REV: N/A DATE: N/A

SHEET 3 OF 4

PREPARED BY: Nanci A. Olson

DATE: 12/16/96

APPROVAL:

SR&MA:

DATE:

DESIGN:

DATE:

SSCS PROJECT MANAGER:

DATE:

CRITICALITY(H/P): 2/2

INTACT ABORT MODE CRIT: N/A

REDUNDANCY SCREENS: A-N/A B-N/A C-N/A

FMEA REFERENCE: SSOR-01

NAME: SSOR

DRAWING REFERENCE: SED16102581

QUANTITY: 1

CIL #	REV	FUNCTION	FAILURE MODE AND CAUSE	FAILURE EFFECT	RATIONALE FOR ACCEPTABILITY
SSOR-01	BASIC	<p>(1) Provides RF duplex voice comm between Orbiter and EMU's.</p> <p>(2) Receives biomed and telemetry from EMU.</p> <p>(3) Provides RF duplex voice comm between Orbiter and Station</p> <p>(4) Provides RF command to Space Station and telemetry from Space Station</p>	<p>FAILURE MODE: Short to case of RF Input or Output at Payload Bay Antenna Port</p> <p>CAUSE: Contamination, vibration, shock, EEF parts failure, or temperature cycle</p> <p>MISSION PHASES: Pre EVA EVA Post EVA Station Rendezvous</p>	<p>SUBSYSTEM: Loss of Transmit and Receive Voice Communications between Orbiter and Station or EMUs. Loss of commands to Station. Loss of data from EMU and Station.</p> <p>INTERFACING SUBSYSTEMS: None</p> <p>MISSION: Terminate EVA. Terminate Station rendezvous.</p> <p>CREW/VEHICLE: No effect.</p> <p>SUCCESS PATHS REMAINING AFTER FIRST FAILURE: 0</p> <p>TIME TO EFFECT: minutes</p>	<p>TEST: (CONTINUED)</p> <p>VIBRATION - 30 sec. per axis minimum 20 Hz - 0.01 g²/Hz 20 to 80 Hz - increasing 3 dB/oct 80 to 350 Hz - constant 0.04 g²/Hz 350 to 2000 Hz - decreasing 3 dB/oct RF Power Output measured before and after each axis.</p> <p>PREINSTALLATION ACCEPTANCE TEST - Performed periodically at JSC prior to delivery of SSOR for Orbiter installation. Includes complete electrical performance with RF output power measured. Unit operated approximately 40 hours during acceptance testing.</p> <p>GROUND INTERVAL(OMDP) TEST: Interval (OMDP) checkout testing is accomplished in accordance with the OMRSD (V74). Tests in the OPF measure RF power output. On the pad, functional verification of audio/RF, but not a performance measurement of output power during EMU checkout.</p> <p>INSPECTION: The SSOR is manufactured in accordance with an approved Quality Assurance Plan. Subassemblies are inspected for conformance with released drawings and standards for parts placement, soldering, and cleanliness.</p>

CRITICAL ITEMS LIST

SYSTEM: COMMUNICATIONS AND TRACKING SUBSYSTEM: SPACE TO SPACE COMMUNICATIONS SYSTEM

ASSEMBLY: SPACE TO SPACE ORBITER RADIO (SSOR) ASS'Y P/N: SED15102581

APPROVAL DATE:

SUPERCEDES REV: N/A DATE: N/A

SHEET 4 OF 4

END ITEM EFFECTIVITY: OV102, OV103, OV104, OV105, AND SUBS.

PREPARED BY: Nanci A. Olson

DATE: 12/16/96

APPROVAL:

SR&MA: _____

DATE: _____

DESIGN: _____

DATE: _____

SSCS PROJECT MANAGER: _____

DATE: _____

CRITICALITY(H/F): 2/2

INTACT ABORT MODE CRIT: N/A

REDUNDANCY SCREENS: A-N/A B-N/A C-N/A

FMEA REFERENCE: SSOR-01

NAME: SSOR

DRAWING REFERENCE: SED16102581

QUANTITY: 1

CIL #	REV	FUNCTION	FAILURE MODE AND CAUSE	FAILURE EFFECT	RATIONALE FOR ACCEPTABILITY
SSOR-01	BASIC	<p>(1) Provides RF duplex voice comm between Orbiter and EMU's.</p> <p>(2) Receives biomed and telemetry from EMU</p> <p>(3) Provides RF duplex voice comm between Orbiter and Station</p> <p>(4) Provides RF command to Space Station and telemetry from Space Station</p>	<p>FAILURE MODE: Short to case of RF Input or Output at Payload Bay Antenna Port</p> <p>CAUSE: Contamination, vibration, shock, EEE parts failure, or temperature cycle</p> <p>MISSION PHASES: Pre EVA EVA Post EVA Station Rendezvous</p>	<p>SUBSYSTEM: Loss of Transmit and Receive Voice Communications between Orbiter and Station or EMUs. Loss of commands to Station. Loss of data from EMU and Station.</p> <p>INTERFACING SUBSYSTEMS: None</p> <p>MISSION: Terminate EVA. Terminate Station rendezvous.</p> <p>CREW/VEHICLE: No effect.</p> <p>SUCCESS PATHS REMAINING AFTER FIRST FAILURE: 0</p> <p>TIME TO EFFECT: minutes</p>	<p>FAILURE HISTORY: Current data can be found in PRACA database.</p> <p>OPERATIONAL USE: Crew is trained to terminate EVA upon loss of all communications with the Orbiter. Rendezvous is terminated with the Space Station if communications are not established by the T1 rendezvous point.</p>