

Failure Modes and Effects Analysis/Critical Items List

Document Number: JSC-38378 Document Rev. No.: C Document Date: 8/26/97
 Title: Risk Assessment Executive Summary Report (RAESR) for the USA SAFER

Item Name: Power/Test Switch Qty: 1 FMEA Number: US-SFR-360
 Item Part Number: 231AT202 ORU Name: SAFER
 Subsystem Name: HCM ORU Part Number: SED33105900-311
 Function: Controls power and test selection.

Item Type Designator: C PG/IP Identifier: N/A
 Reference Designator/Find No.: N/A Drawing Number: SED33106100
 Logistics Control Number: N/A

End Item Name: SAFER
 End Item Capability: Six degrees of freedom through 24 thrusters, each rated at 0.8 ± 0.08 lbs. force in vacuum.
 End Item Function: Provides emergency EVA self-rescue for separated crewmember.
 ISS Zone: EVA Shuttle Zone: EVA

Criticality

Critical Item: Yes: No: Criticality Category: ISS Shuttle
 Success Success Paths Remaining: 1R 1R/3
 Paths:

Failure (Mode, Cause, Detection, Corrective Action)

Failure Mode: Power/Test Switch fails to initiate power to PSA.
Failure Mode Code:
Failure Cause: Switch Failure, EEE part failure, short/open circuit, contamination, software error, radiation event, EMI.
Failure Detection:
Flight: IVA – If failure is detected during IVA checkout, use back-up SAFER if available.
 EVA – Cycle power. If not successful, no other corrective action.
Ground: Functional Test.
Time To Detect Quantity: 10 **Time To Detect Units:** Seconds
Correcting Action: Cycling the power switch may restore power. If a failure is detected during the IVA checkout, the back-up SAFER (if available) will be used.
Remarks: None
Failure Effect Phase: EVA Operations **Affected Stage(S):** EVA Operations

Failure Effect

On ORU/Assembly:
First/Second Failure: Inadvertent EVA crewmember separation.
Third (this) Failure: Unable to arrest motion.
On Subsystem/Next Assembly: No power to SAFER avionics.
On End Item/Segment: Unable to arrest motion. Possible loss of mission objectives if SAFER required for EVA.
On Crew/ISS: Possible loss of crewmember. Possible damage to EMU/Orbiter/ISS.
Time To Effect Quantity: 1 **Time To Effect Units:** Minutes

Redundancy Screen

ISS		(Shuttle)			
Checkout Pre-Launch	(A):	Pass			
Checkout On-Orbit	(B):	N/A			
Detection Flight Crew:		Pass	Or	Detection Ground Crew:	Fail
Loss Of Redundancy From A Single Cause	(C):	N/A			